




Husqvarna FS 520

Series of floor saws with engine options from 13 to 24 hp. The floor saws are developed with a clear focus on ergonomics and user friendliness, featuring many innovative solutions that make your job easier. Their unique transmission makes them ideal for more demanding jobs, despite their compact size.



Features Husqvarna FS 520

- Husqvarna's floor saws are robust, well designed and easy to use thanks to features as protective cage, lift bail and cutting depth indicator.
- Patent-pending raise/lower assist system, using springs.
- Specially designed to last longer than conventional belts. Our Poly-V Belt requires less re-tensioning and provides better power transmission.
- Gas Honda up to 24 hp engines with electric start.
- Self-contained differential drive system eliminating drive gear from rear wheels and related wear. It is simple to handle and maintain.
- Left and right cutting capability.
- Integrated tool box.
- Optional water tank (6.6 gal) sits above the motor.
- Integrated fuel tank (2.2 gal) for extended use.
- Complete console with engine start/stop switch and throttle, transmission control lever, tachometer/timer.
- Quick belt tensioning system.

TECHNICAL SPECIFICATION

| | |
|--|--|
| Motor spec | GX620 |
| Max output (As rated by the engine manufacturer) | 13.42 kW / 18 hp |
| Cylinders | 1 |
| Number of strokes | 4-stroke engine |
| Cylinder displacement | 37.5 cu.inch |
| Cylinder bore | 3.03 inch |
| Cylinder stroke | 2.6 inch |
| Fuel tank volume | 2.2 gal. |
| Air filter type | Cyclone dry dual |
| Starter | Electric |
| Engine cooling | Air |
| Belt | Poly V |
| Number of belts | 16 |
| Oil capacity, l | 1.4 lit |
| Output RPM | 2620 rpm |
| Diamond blade, max | 20" |
| Max cutting depth | 7.625 inch |
| Spindle diameter | 1" |
| Blade depth control | Handwheel |
| Blade shaft diameter | 1.1875 inch |
| Blade shaft drive | Poly-V |
| Blade flange | 4.5" |
| Max. saw travel speed | 7.62 fpm |
| Arbor size | 1" |
| Axle front | 0.9 inch |
| Rear axle diameter | 0.9 inch |
| Transmission type | Hydros. Transaxle |
| Transmission speed | 0-26 |
| Transmission speed | 0-80 fpm |
| Handle bars | Multi position |
| Primary wheel size | Outside diameter: 5 Wheel width: 1.5 Inner bore: 0.75" |
| Secondary wheel size | Outside diameter: 10 Wheel width: 3 Inner bore: 0.875" |
| Blade guard attachment | Slip-on |
| Blade guard type | Slip-on |
| Weight | 493 lbs |
| Weight incl. packaging | 580 lbs |
| Product size, LxWxH | 66x26x42 inch |
| Sound power level, guaranteed (LWA) | 96 dB(A) |
| Sound pressure | 106 dB(A) |
| Hand arm vibration (Aeq) | 3 m/s ² |